


# 316SS

## Check Valves



### O-RING POPPET VALVES




#### FEATURES & BENEFITS

- Compact length
- Spring-loaded 2 or 10 PSI
- Full range of sizes 1/4" to 1" MNPT
- All 316 stainless steel construction
- Viton® or PTFE O-Rings as standard (other materials available)
- Pressures to 2,500 PSI
- Temperatures -15° to +400°F
- Usable on metering pumps
- Usable as injection line check valves
- Custom valve inquiries invited



### BALL CHECK VALVES



#### FEATURES & BENEFITS

- Compact length
- Spring-loaded 2 or 10 PSI
- Full range of sizes 1/4" to 1" MNPT
- All 316 stainless steel construction
- Other ball materials available
- Easily disassembled for inspection or cleaning
- Pressures to 2,500 PSI
- Temperatures -15° to +650°F
- Usable on metering pumps
- Usable as injection line check valves
- Custom valve inquiries invited

### O-RING POPPET MODELS

VALVE SIZE	CRACKING PRESSURE	PART NUMBER	SIZE "S"	HEX "H"	"L"	CV
1/4	2 LB.	A00101-01	1/4-18	5/8	1 7/8	.46
	10 LB.	A00101-02				
3/8	2 LB.	A00102-01	3/8-18	3/4	2 1/8	1.42
	10 LB.	A00102-02				
1/2	2 LB.	A00103-01	1/2-14	7/8	2 1/2	1.82
	10 LB.	A00103-02				
3/4	2 LB.	A00104-01	3/4-14	1 1/8	2 5/8	6.02
	10 LB.	A00104-02				
1	2 LB.	A00105-01	1-11 1/2	1 1/2	3 1/8	12.80
	10 LB.	A00105-02				

### BALLCHECK MODELS

VALVE SIZE	CRACKING PRESSURE	PART NUMBER	"L"	HEX "H"	"S" MPT	BALL	"P"	CV
1/4	2 LB.	A00031-01	1 1/2	5/8	1/4-18	.250	.200	.56
	10 LB.	A00031-02						
3/8	2 LB.	A00032-01	1 3/4	3/4	3/8-18	.312	.250	.83
	10 LB.	A00032-02						
1/2	2 LB.	A00033-01	2 1/4	7/8	1/2-14	.437	.335	1.49
	10 LB.	A00033-02						
3/4	2 LB.	A00034-01	2 1/2	1 1/8	3/4-14	.562	.442	2.98
	10 LB.	A00034-02						
1	2 LB.	A00035-01	2 3/4	1 3/8	1-11 1/2	.750	.530	5.65
	10 LB.	A00035-02						